

PF8

Printer Heat Settings

200 dpi (PF8d and PF8t)

North America

Direct Thermal Media

	Heat Setting	Max Rec Print Speed (mm per second / inches per second)	
		Picket	Ladder
Duratherm II	10	100 / 4	100 / 4
Duratherm III	8	100 / 4	100 / 4
Duratherm II Tag	10	100 / 4	100 / 4
Duratherm Lightning	6	100 / 4	100 / 4
Duratherm IR	7	100 / 4	100 / 4

Thermal Transfer Media

	Heat Setting	Max Rec Print Speed (mm per second / inches per second)		
		Picket	Ladder	
TMX1407	Duratran II	7	100 / 4	100 / 4
	Duratran II Syntran	6	100 / 4	100 / 4
	Duratran II Kimdura	8	100 / 4	100 / 4
	Duratran II Valeron Tag	8	100 / 4	100 / 4
TMX2202	Duratran II	8	100 / 4	100 / 4
	Duratran II Kimdura	10	100 / 4	100 / 4
	Duratran II Syntran	8	100 / 4	100 / 4
	Duratran II Valeron Tag	11	100 / 4	100 / 4
TMX3202	Duratran II Gloss Polyester	8	100 / 4	100 / 4



PF8

Printer Heat Settings

300dpi (PF8t model only)

North America

Direct Thermal Media

	Heat Setting	Max Rec Print Speed (mm per second / inches per second)	
		Picket	Ladder
Duratherm II	12	50 / 2	50 / 2
Duratherm III	10	50 / 2	50 / 2
Duratherm Lightning	8	50 / 2	50 / 2
Duratherm IR	10	50 / 2	50 / 2

Thermal Transfer Media

	Heat Setting	Max Rec Print Speed (mm per second / inches per second)		
		Picket	Ladder	
TMX1407	Duratran II	0	50 / 2	50 / 2
	Duratran II Syntran	0	50 / 2	50 / 2
	Duratran II Kimdura	1	50 / 2	50 / 2
	Duratran II Valeron Tag	2	50 / 2	50 / 2
TMX2202	Duratran II	2	50 / 2	50 / 2
	Duratran II Kimdura	3	50 / 2	50 / 2
	Duratran II Syntran	1	50 / 2	50 / 2
	Duratran II Valeron Tag	3	50 / 2	50 / 2
TMX3202	Duratran II Gloss Polyester	6	50 / 2	50 / 2

The above settings represent guidelines for general printing conditions. Some formats will require adjustment of the heat setting and/or print speed to properly image.

The maximum recommended print speed is a condition of the Intermec print head replacement program. Failure to adhere to these recommendations may nullify the print head warranty.



Copyright © 2012 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. 03/12

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

Intermec[®]